

Bellmarine designed hard and software which easily combine with the powerful range of nautical products of Raymarine. The Axiom multifunction displays deliver the speed and simplicity of the Lighthouse III user interface, which ensures smooth operation of the touchscreen.

Now it is possible to integrate your electric propulsion 1 or 2 Bellmarine motor system information into your complete boat system and have everything on one well-arranged screen including GPS speedometer and chart plotter.

With the standard integrated Wi-Fi function, you will always have an extra screen on your tablet or smartphone.



Raymarine display – Axiom+ 7, 9 & 12

Our system is supplied complete with special motor controller software and adapter cable installed

Your choice is supplied with the Actisense NMEA 2000® backbone in a single device and is pre assembled with the Bellmarine custom page.

- **Every display / cable set is supplied with the Actisense NMEA2000 backbone and 2m cable**
The standard length of the cable set = 5 meter.
- Adding the 'NMEA2000 configuration kit' for visualizing all system features see on the option kits

PRODUCT CODE	MODEL	DESCRIPTION
BV101516A	Bellmarine MFD Axiom+ 7	7" Multi functional display incl. integrated Wi-Fi incl. A2K-SBN4, cable set
BV101517A	Bellmarine MFD Axiom+ 9	9" Multi functional display incl. integrated Wi-Fi incl. A2K-SBN4, cable set
BV108128	Bellmarine MFD Axiom+ 12	12" Multi functional display incl. integrated Wi-Fi incl. A2K-SBN4, cable set

- Models with integrated RealVision sonar module on request



Accessories

Display

For every System a display and cable set is highly recommended for monitoring and control.

- With cable adapter



TF Easy



TF1



TF Pro



TF2

PRODUCT CODE	DESCRIPTION	
BVTE3281C	TF Easy	Display with battery status indication, motor power, motor rpm, motor temperature, controller temperature, eco meter, battery amps, battery voltage and mode selection. For any type of battery. Incl. cable set for monitoring and control
BVTE3281D	TF Pro - Full Colour	Colour display with battery status indication, motor power, motor rpm, motor temperature, controller temperature, eco meter, battery amps, battery voltage and mode selection. For any type of battery. Incl. cable set for monitoring and control
BVTE3281A	TF1 - Full Colour	Colour display with battery status indication, motor power, motor rpm, motor temperature, controller temperature, eco meter, battery amps, battery voltage and mode selection. For any type of battery. Incl. cable set for monitoring and control
BVTE3281B	TF2 - Full Colour	Colour display for twin screw system with battery status indication, motor power, motor rpm, motor temperature, controller temperature, eco meter, battery amps, battery voltage and mode selection. For any type of battery. Incl. cable set for monitoring and control
BVTE3280A	Extension cable length 2,5m	Signal cable between dashboard and engine room
BVTE3280B	Extension cable length 5m	
BVTE3280C	Extension cable length 10m	
BVTE3280D	Extension cable length 15m	
BVTE3280E	Extension cable length 20m	



Motor controller

Extension

